

LABORATORI METROLOGICI per misure di TEMPERATURA, UMIDITA' e PRESSIONI

CENTRO DI TARATURA LAT N° 123 per: Temperatura da -80°C a 1550°C Umidità da 10% a 90%

Tarature esterne di temperatura

Via Mulini Esterna 18, 41012 Carpi (Mo) Tel. +39-059.663006 Fax. +39-059.663128 P.I. 02059800363 E-Mail: sit123@camarelettronica.it Web: http://www.camarelettronica.it

Cod. Fiscale, Partita IVA e Reg. Imprese di Modena: 02059800363 - R.E.A. di MO 262666 - Cap. Soc. Euro 20.800,00 int. versato

MINI 1 WAY



Data logger for Single Trip (not rewritable)

Mini 1 WAY is a 1-channel data logger with internal temperature sensor with a working range from -40°C to 80°C, direct connection to PC and automatic creation of a PDF file with the recorded data. The logger can store 13,000 measurements with an interval of 1 second to 24 hours. It can be pre-programmed with predefined alarm thresholds or can be programmed on request, according to customer specifications. Supplied in a pack of 10 pieces.

TECHNICAL FEATURES

Temperature
Internal
-40 ÷ 80°C
0,01°C
± 0,3°C from -10°C to +80°C ± 0,5°C from -40°C to -10°C
13.000 readings
USB for direct connection to PC
free download
IP65 - The logger is supplied inside a sealed sachet which
guarantees watertightness
3 V lithium battery, not replaceable
78 x 48 x 9 mm
16 g
Supplied in a pack of 10 pieces